

RP-342 "BLACK" Military-Grade Rust Preventive Spray

Our Strongest, Thickest, Longest-Lasting (and Fastest-Drying) Rust Preventive!

- * One coat protects all metals, iron, steel (stored Indoors or Outdoors) for Years!
- * Our most concentrated, longest-lasting (and bestselling!) Rust Preventive Spray.
- * Produces a dry-to-the-touch, **BLACK** protective wax coating that **CONCEALS** unsightly surfaces.
- * Fast-Drying formula allows for more convenient, mess-free and quicker handling, shipping or packaging.
- * Withstands severe outdoor exposure/environments, salt-laden atmospheres, acid and caustic fumes.
- * Repels water and will not wash off in salt water environments or via pressure wash.
- * Will not crack, craze, blister, peel or flake and remains slightly flexible over time.
- * Exceptional Vehicle Undercoating - undercarriages, wheel wells, bumpers, frames...
 - Reliable, long-term protection from salt, road chemicals & debris, extreme temps, etc.
- * Aggressively adheres to imperfect surfaces and offers self-abrading characteristics.
- * Modeled after Military Specifications: MIL-PRF-16173, Grade 4 and MIL-C-83933.

COMMON APPLICATIONS INCLUDE (but are not limited to):

- * Parts, equipment and machinery storage
- * Vehicle undercarriage / undercoating (cars, buses, trucks, etc.)
- * Heavy machinery, equipment, parts & tools
- * Packaging
- * Dies, molds, lathes, shafts and beams
- * Offshore Drilling equipment, platforms & infrastructure
- * Farm implements
- * Overseas transportation
- * Boat shafts and propellers
- * Marine fittings
- * Rifle & other firearms preservation/storage
- * Garden tools & lawn mower blades
- * and any other surface or part that might rust on you...



12oz. aerosol can
Part #: RP-342-BLK

APPLICATION:

Prior to application, ensure surface is reasonably clean and dry (not oily or greasy). Spray thin uniform film. For applications requiring long storage or protective durations, a second coating is recommended after initial coat is completely dry. Complete setting of protective coating takes approximately 1 hour. Typical first application Dry Film Thickness is 2.0 MILS (51 Microns).

***** IMPORTANT ***: When applying to VERTICAL SURFACES, apply two or more coats to achieve uniform Black appearance. Apply heavy first coat and let fully dry before applying additional coat(s). Review safety data sheet for all suggested safety requirements.**

REMOVABILITY:

RP-342 "BLACK" can be easily removed with any over-the-counter petroleum solvent. Examples include mineral spirits, paint thinner, naphtha, diesel fuel, or our very own Ultimate Cosmoline Remover.

MILITARY SPECIFICATIONS:

RP-342 "BLACK" is modeled after military specifications: MIL-PRF-16173E Grade 4, Class 1 and MIL-C-83933

To Re-Order, Click or Call:
www.CosmolineDirect.com
or (866) 802-2906

This product is also available in CLEAR.
See RP-342 "HEAVY" on the other side.

